

## UV-P (Suqian)

Technical DataSheet | Supplied by Suqian Unitechem

UV-P by Suqian Unitechem is a high-performance UV absorber, effectively absorbing 290-400nm UV light. It is mainly used in PVC, PP, unsaturated resin, PC, PMMA, PE, ABS resin, epoxy resin and fiber resin.

**Product Type** Light Stabilizers / UV Absorbers

**CAS Number** 2440-22-4

**Product Status** COMMERCIAL

**Applications/ Recommended for** PMMA  
PP  
PVC  
PE  
ABS  
Epoxy, Epoxide Resin  
PC

## UV-P (Suqian) Properties

Property	Value & Unit	Test Condition	Test Method
<b>Molecular Weight, Mw</b>	225.3		
<b>Melting Point</b>	125 - 130 °C		
<b>Volatility</b>	< 0.5 %		
<b>Weight Loss Point</b>	163 °C	At 5.0%	

## Compatibility with other products

Find products that are predicted to be compatible with UV-P (Suqian).

This list of compatible products is generated out of estimated HSP values. A practical determination of these HSP values

would provide higher certainty.

[Learn more about Hansen Solubility Parameters \(HSP\) and their use in predictive formulation](#)

---

### Help us improve the Universal Selector

You can't find what you are looking for? Please report missing products / suppliers, point out errors, or simply tell us how we could make the Universal Selector better.