PANGANG TITANIUM

R-298 rutile titanium dioxide

R298 is a multi-purpose rutile TiO₂ pigment is known for its low oil absorption, high gloss, high tinting strength, durability, and dispersability. Produced by the Sulfate process, with a very fine particle size, it has excellent hiding power, blue tint undertone.

R298 has a zirconium and Al2O3 inorganic surface treatment, in combination with a special organic coating. It is well suited for both waterborn and solventborn coating, ink applications.

Α	n	n	li	cat	io	ns
, ·	\sim	\sim		out	\cdot	110

Architectural exterior coatings

Exterior industrial finishes

Powder coatings Container coatings Coli coatings

Ink

Properties

High dispersability in solvent and waterborne systems

Excellent gloss retention High tinting strength Bluish undertone

Product Characteristics

TiO ₂ content %	≥93.5
Brightness %	≥95.0
Volatile at 105 °C	≤0.5
pH	6.0-9.0
Oil absorption	≤19
Residue on sieve (45 um)	≤0.02
Tinting strength Reynolds number	≥1920
Rutile content	≥98
Dispersibility	≥6.50
ISO591-1:2000(E)	R2
ASTM D476-00	V

All information is based on data obtained from the manufacturer or recognized technical sources. The information is believed to be accurate. We make no representation or warranty, express, or implied, concerning the accuracy or sufficiency of the information. We are not liable for any damages resulting from the use of the information.

PANGANG TITANIUM INDUSTRY CO.,LTD.

www.pangang-titanium.com

email: sale@ pangang-titanium.com